

Altus NR3

Compact GNSS Rover for Surveying & GIS Applications



The Altus NR3 smart antenna combines easy-to-use, quad-constellation RTK with an unrivalled communications toolset for a successful survey or GIS project every time.

KEY FEATURES

- ▶ **Robust, light and portable GNSS receiver**
- ▶ **Quad-constellation, multi-frequency all-in-view RTK positioning**
- ▶ **AIM+ anti-jamming and monitoring system**
- ▶ **Easy setup and one-touch logging**
- ▶ **Robust RTK position accuracy and L-band (PPP) support**
- ▶ **All-in-one base and rover operation**
- ▶ **L-band for SECORX worldwide corrections**



BENEFITS

Exceptional Performance and Reliability

Quad-constellation, multi-frequency RTK that sets the new standard in positioning performance. It includes APME+ industry-leading multipath technology and IONO+ to ensure position accuracy under the most intense ionospheric activity. These features together with LOCK+, to maintain tracking during mechanical shocks or vibrations, combine to offer the best possible quality of measurements for Altus NR3's GNSS position calculations.

Interference Robustness

The Altus NR3's AIM+ is quite simply, the most advanced on board anti-jamming technology on the market. It can suppress the widest variety of interferers, from simple continuous narrowband signals to the most complex wideband and pulsed jammers. The RF spectrum can be viewed on the Web UI in real-time in both time and frequency domains.

Use Your Own Device

Thanks to Septentrio's open architecture, the Altus NR3 is fully compatible with leading third-party hardware and software solutions thus maximising the use of existing equipment while driving down the cost of ownership over the lifetime of the device.

Collection Made Simple

Thanks to its advanced communication (4G/LTE), you can unify high-accuracy GNSS data with the power of data collection using either SurvCE/SurvPC or PinPoint Data collector. SurvCE/SurvPC allows advanced survey data collection while PinPoint-GIS enables simple data collection from the Altus NR3 directly to the cloud.

Altus NR3

FEATURES

GNSS technology

448 hardware channels for simultaneous tracking of all visible satellite signals:

- ▶ GPS: L1, L2, L5
- ▶ GLONASS: L1, L2, L3
- ▶ Galileo¹: E1, E5ab, AltBoc
- ▶ BeiDou¹: B1, B2
- ▶ SBAS: EGNOS, WAAS, GAGAN, MSAS, SDCM (L1, L5)
- ▶ IRNSS¹: L5
- ▶ QZSS: L1, L2, L5
- ▶ L-band¹

Support for PPP (SECORX)²

DGNSS and RTK (base and rover)¹

Septentrio's patented GNSS+ technologies

AIM+ unique anti-jamming and monitoring system against narrow and wideband interference

IONO+ advanced scintillation mitigation

APME+ a posteriori multipath estimator for code and phase multipath mitigation

RAIM (Receiver Autonomous Integrity Monitoring)

LOCK+ superior tracking robustness under heavy mechanical shocks or vibrations

Connectivity

Integrated Bluetooth (2.1 + EDR/4.0)

Integrated WiFi (802.11b/g/n) access point and client mode³

2 4G LTE models:

- ▶ **EU 4G¹⁷**: 4G LTE Cat 1 (B3, B8, B20), 2G Dual Band GSM/GPRS/EDGE (900/1800) or
- ▶ **NA 4G¹⁸**: 4G LTE Cat 1 (B2, B4, B5, B12, B17) 3G UMTS/HSPA (850/900/1900/2100), 2G Quad Band GSM/GPRS/EDGE

Dynamic DNS³ and remote access to receiver

NTRIP (v1 and v2) client server and caster

Direct IP and Data call (CDS) calling and accepting mode³

1 x 9-pin Lemo connector for:

- ▶ Full-speed USB (host-with access to internal disk, TCP/IP communication and with 2 extra serial ports)
- ▶ 1 High-speed serial port (RS232) ideal for external UHF radio or custom integrations⁴

Data formats and storage

16 GB internal memory

NMEA 0183 v2.3, v3.01 and v4.0 output

Septentrio Binary Format (SBF), fully documented and with sample parsing tools

Corrections input and output:

- ▶ RTCM v2.x and 3.x (MSM included)
- ▶ CMR v2.0 and CMR+ (CMR+ input only)

MODELS

Altus NR3 Full-Const: All-constellations RTK network rover and base

Altus NR3 C: GPS/GLO RTK network rover and base

Altus NR3 Base: RTK Base station only

All models available in European¹⁷ or

North American¹⁸ versions.

PERFORMANCE

Position accuracy^{5,6}

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m
DGNSS	0.4 m	0.7 m
SECORX C (PPP) ^{2,7}	4 cm	6 cm
SECORX D (PPP) ^{2,7}	4 cm	9 cm

RTK performance^{1,5,6,8}

Horizontal accuracy	0.6 cm + 0.5 ppm
Vertical accuracy	1 cm + 1 ppm

Velocity accuracy^{5,6}

3 cm/s

Static and rapid static

Horizontal	3 mm + 0.5 ppm
Vertical	5 mm + 0.5 ppm

Static and high precision⁹

Horizontal	3 mm + 0.1 ppm
Vertical	3.5 mm + 0.4 ppm

Maximum update rate¹⁰

Position (Standalone, SBAS, DGNSS)	20 Hz
Position (RTK)	10 Hz
Measurements only	20 Hz

Time to first fix

Average time to fixed RTK	< 7 s
Cold start ¹¹	< 55 s
Warm start ¹²	< 30 s
Re-acquisition	avg. 1 s

Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

STANDARD SYSTEM COMPONENTS

- 1 x Altus NR3
- 4 x Lithium-ion batteries (standard 18650 Li-ion batteries with protection circuit)
- 1 x USB data cable
- 1 x Altus NR3 battery charger (4-battery capacity)
- 1 x Battery charger cable for cigarette lighter



PHYSICAL AND ENVIRONMENTAL

Size 167 x 69 mm / 6.5 x 2.7 in

Weight¹³ 820 g / 1.8 lb

Internal battery 2 x 3.6 V, 3400 mAh (Li-ion)

Battery lifetime¹⁴ 6 hours

External power input⁴ 9-30 V DC

Operating temperature¹⁵ -30° C to +75° C
-22° F to 167° F

Storage temperature -40° C to +75° C
-40° F to 167° F

Shock/drop 2 m / 6.6 ft

Certification CE, FCC¹⁸ Class B Part 15

Waterproofing IP67

COMPATIBLE SOFTWARE

- ▶ Embedded Web UI with full control and monitoring functionality
- ▶ Full support for Carlson SurvCE/SurvPC
- ▶ Support for a large variety of survey, GIS and post-processing software applications
- ▶ Mobile PinPoint-GIS App for basic data collection, easy monitoring and control allowing overriding location of Android GNSS applications
- ▶ On board data collection using either Septentrio's PinPoint-GIS CSV point data collection¹ or Esri's ArcGIS® Online¹⁶

¹ Optional feature

² Service subscription required

³ Allows communication between base and rover

⁴ Power and serial communication provided from Lemo connector with dedicated cable

⁵ Performance depends on environmental conditions

⁶ RMS level

⁷ After convergence

⁸ Baseline < 40 km / 24.9 miles

⁹ Long occupations and precise ephemeris

¹⁰ Update rate via Bluetooth limited to 10 Hz

¹¹ No information available (no almanacs, no approximate position)

¹² Ephemeris and approximate position known

¹³ Weight: 740 kg / 1.6 lb without batteries

¹⁴ Unlimited operation time thanks to hot-swappable batteries

¹⁵ At temperatures below -20° C / -4° F, an external power supply may be required

¹⁶ Required an ArcGIS® Online subscription

¹⁷ Applicable to the Altus NR3 European version (4G compatibility in Europe and other regions)

¹⁸ Applicable to the North American version (4G compatibility in North America and other regions)

EMEA (HQ)

Greenhill Campus
Interleuvenlaan 15i
3001 Leuven, Belgium

+32 16 30 08 00

septentrio.com

Americas

Los Angeles, USA

sales@septentrio.com

Asia-Pacific

Melbourne, Australia
Shanghai, China
Yokohama, Japan

